

GS-P646-F28

4MP H.265+ True WDR EXIR Fixed IR Dome Network Camera (2.8mm Lens)



- Up to 4MP high resolution
- 2.8mm fixed lens
- 3D Digital Noise Reduction
- DC12V & PoE
- Up to 30m IR range
- IK 10
- Bit rate mode: CBR and VBR
- Dual video streams
- 120dB True WDR
- Support on-board storage, up to 128GB
- Support H.264+
- IP67 weather-proof protection
- -S: Audio/Alarm IO

| | |
|--------------------------------|--|
| Image Sensor | 1/3" Progressive Scan CMOS |
| Min. Illumination | Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR |
| Shutter Speed | 1/3s to 1/10,000 s |
| Slow Shutter | Yes |
| Auto-Iris | No |
| Day&Night | IR cut filter |
| Digital Noise Reduction | 3D DNR |
| WDR | 120dB |
| 3-Axis Adjustment | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355° |
| Focal length | 2.8 |
| Aperture | F1.6 |
| Focus | Manual |
| FOV | 2.8 mm: horizontal FOV: 98°, vertical FOV: 55°, diagonal FOV: 114° |
| Lens Mount | M12 |
| IR Range | Up to 30 m |
| Wavelength | 850nm |
| Video Compression | Main stream: H.265/H.264 Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264 |
| H.264 Type | Main Profile/High Profile |
| H.264+ | Main stream and sub-stream support |
| H.265 Type | Main Profile |
| H.265+ | Main stream and sub-stream support |
| Video Bit Rate | 32 Kbps to 16 Mbps |
| Audio Compression (-S) | G.711/G.722.1/G.726/MP2L2/PCM |
| Audio Bit Rate | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2) |
| Behavior Analysis | Line crossing detection, intrusion detection |
| Face Detection | Yes |
| Region of Interest | 1 fixed region for main stream and sub-stream |
| Max. Resolution | 2560 × 1440 |
| Main Stream | 50Hz:25fps (2560 × 1440, 2304 × 1296, 1920 × 1080) 60Hz: 30fps (2560 × 1440, 2304 × 1296, 1920 × 1080) |
| Sub-Stream | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240) |
| Third Stream | 50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240) |

| | |
|--------------------------------------|---|
| Image Enhancement | BLC/3D DNR |
| Image Setting | Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser |
| Target Cropping | No |
| Day/Night Switch | Auto/Schedule/Triggered by alarm in (-S) |
| Network Storage | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR |
| Alarm Trigger | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD erro |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| General Function | One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP address lter |
| Firmware Version | V5.5.2 |
| API | ONVIF (PROFILE S, PROFILE G), ISAPI |
| Simultaneous Live View | Up to 6 channels |
| User/Host | Up to 32 users 3 levels: Administrator, Operator and User |
| Client | iVMS-4200, Hik-Connect, iVMS-5200 |
| Web Browser | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+ |
| Audio (-S) | 1 input (line in/mic.in), 1 output (line out), terminal block, mono sound |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet port |
| Alarm (-S) | 1 input, 1 output (up to 12 VDC, 30 mA), terminal block |
| Video Output | No |
| On-board storage | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB |
| SVC | H.264 and H.265 encoding |
| Reset Button | Yes |
| Environment Noise Filtering | Yes |
| Audio Sampling Rate | 16 kHz/32 kHz/44.1 kHz/48 kHz |
| Operating Conditions | -30 °C –60 °C (-22 °F –140 °F), Humidity 95% or less (non-condensing) |
| Power Supply | 12 VDC ± 25%, Φ 5.5 mm coaxial power plug PoE (802.3af, class 3) |
| Power Consumption and Current | 12 VDC, 0.5A, max. 6W PoE (802.3af, 37V to 57V), 0.2A to 0.1A, max. 7.5W |
| Protection Level | IP67, IK10 TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection |
| Material | Metal |
| Dimensions | Camera: Φ 111 × 82.4 mm (Φ4.4" × 3.2") Package: 134 × 134 × 108 mm (5.3" × 5.3" × 4.3") |
| Weight | Camera: Approx. 610 g (1.3 lb.) With Package: Approx. 820 g (1.8 lb.) |

