

# GS-PA12-FEA

## 12MP Network Fisheye Camera

### Key features

GS-PA12-FEA is a fisheye network camera capable of providing a 360 degree panoramic image of its surveillance scene. The progressive scan CMOS sensor provides high-resolution images of up to 4000 × 3072. Up to 14 live view display modes, designed for 3 mount types and 2 decoding modes, meet the major needs of different preference. IR range of 15 meters provides good visibility in low or even zero-light environment.

- 1/1.7" Progressive Scan CMOS
- Max. 4000 × 3072 @20fps
- Up to 14 live view display modes
- Digital WDR
- Up to 15m IR range
- Built-in microphone and speaker
- 2 behavior analyses, 1 statistic



### Features and Functions

#### Smart

- 2 behavior analyses, line crossing detection and intrusion detection
- 1 statistic, heat map
- Smart recording: Support edge recording and dual-VCA
- Smart encoding: Support low bit rate, low latency, ROI enhance encoding

#### Image

- Max. 4000 × 3072 @20fps
- Support live view image decoded by hardware and software
- Support up to 14 display modes in total
- Streaming smoothness setting for different requirements of image quality and fluency
- Support H.264+/H.264/MJPEG video compression, multi-level video quality configuration; support Baseline Profile/Main Profile/High Profile H.264 encoding complexity
- Multiple OSD color: Black & white self-adaptive; Custom
- Digital WDR is supportable for backlight environment
- Support BLC

## System

- Support ONVIF (profile E/profile G), ISAPI protocol
- Support dual streams, and support 20 channels live view at the same time
- Lightning protection, surge protection, voltage transient protection, anti-static protection

## Interface

- Support standard 128G microSD/SDHC/SDXC card storage
- Support 10M/100MEthernet port. Support RS-485
- Support Audio I/O, support stereo audio
- Support Alarm I/O

## Security

- Support three-level user authentication management, user and password authorization, and IP address filtering
- Support security certificate as HTTPS
- Lock user IP after certain times failed login attempts

## Specifications

GS-PA12-FEA	
<b>Camera</b>	
Image Sensor	1/1.7" Progressive Scan CMOS
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0.04 Lux @ (F2.4, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s – 1/100,000 s
Slow Shutter	Support
Lens	2 mm @F2.4, horizontal field of view: 180° (wall mount), 360°(ceiling mount), 360°(table mount)
Lens Mount	M12
Day &Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	Digital WDR
<b>Compression Standard</b>	
Video Compression	Mainstream: H.264 Sub stream: H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Support only when the display mode is Fisheye View
Video Bit Rate	256Kbps – 16 Mbps
Audio Compression (-S)	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
<b>Image</b>	
Max. Resolution	4000×3072
Fisheye View Main Stream Max. Frame Rate	50Hz: 20fps (4000× 3072), 25fps(3072 ×3072, 2560 × 2560) 60Hz: 20fps (4000× 3072), 24fps(3072 ×3072), 30fps(2560 × 2560)
Fisheye View Main Stream Max. Frame Rate	50Hz: 12.5fps (720 ×720,704 ×576) 60Hz: 15fps (720 ×720, 704 ×480)
Image Enhancement	BLC/3D DNR
Image Setting	Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Region of Interest	Support 3 fixed region for each stream
Day/Night Switch	Auto/Schedule/Triggered by Alarm In
Picture Overlay	LOGO picture can be overlaid on video with 128×128 24bit bmp format

<b>Live View Display</b>	
Mount Type	Support table, wall, and ceiling
Decoding Mode	Support hardware decoding and software decoding
Display Mode	Support 14display modes in total (including display modes of different mount types and decoding modes): Fisheye View, 180 Panorama View, 4PTZ, Fisheye + 3PTZ, 360 Panorama View, 360 Panorama + PTZ, 360 Panorama + 3PTZ, 360 Panorama + 6PTZ, 360 Panorama + 8PTZ, 2PTZ, Fisheye + 8PTZ, Panorama View, Panorama + 3PTZ, Panorama + 8PTZ
<b>Audio</b>	
Environment Noise Filtering	Support
Audio I/O	Support
Audio Sampling Rate	Max.48kHz
<b>Smart Feature-set</b>	
Intrusion Detection	Enter and loiter in a pre-defined virtual region, up to 4 pre-defined virtual regions supported
Line Crossing Detection	Cross a pre-defined virtual line, up to 4 pre-defined virtual lines supported
Heat Map	A graphical representation of density of visit in a configured area
<b>Network</b>	
Network Storage	Support microSD/SDHC/SDXC card (128G),local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflicted, illegal login, HDD full, HDD error
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General Function	One-key reset, anti-flicker, heartbeat, password protection, privacy mask, watermark, IP address filter
Standard	ONVIF(PROFILE S,PROFILE G),ISAPI
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100MEthernet port With -S model: 1 RS-485 interface.
Audio Input	1 3.5mm audio interface, Mic in/Line in (with -A model); 1 built-in microphone by default, -42dB
Audio Output	1 3.5mm audio output interface 1 built-in speaker by default, support echo cancellation
Alarm	1 input, 1output (up to DC24V 1A or AC110V 500mA)
On-board storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Reset Button	YES
<b>General</b>	
Operating Conditions	Indoor temperature: -10 °C to+50 °C (14 °F -122 °F) With -E model: Outdoor temperature: -30 °C -60 °C (-22 °F -140 °F) Humidity 95% or less (non-condensing)
Power Supply	DC 12 V± 10%, 0.78A PoE (802.3af, class 3), 0.33 -0.21A
Power Consumption	Max. 14.7W
IR Range	15 m
Dimensions	164×152.8×43.8 mm(6.46"×6.02"×1.72")
Weight	1400g (3.09lbs)