

DS-K1107M

Card Reader

MAIN FEATURES

- Equipped with the 32-bit high-speed processor
- RS-485 and Wiegand(W26/W34) protocol
- The card reading frequency is 125KHz and the number of ID card can be read
- Meets the standard of ISO 14443-A and the card reading frequency is 13.56MHz. The number and content of Mifarecard can be read
- Supports tampering alarm
- RS485 and Wiegand(W26/W34) protocol;
- Tamper-proof alarm
- Built-in buzzer for identifying the reading status
- Online upgrade function
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader



Specifications

DS-K1107M	
Power Supply	12V DC
Power Consumption	≤2W
Processor	32-bit
Reading Range	≥5cm
ID Settings	Setting by the DIP Switch on the Main Board
Communication Interface	RS-485 / Wiegand(DIP Switch)
Audio Alert	Beeper
Keypad	No Keypad
LED Indicator	Power Indicator; Status LED Indicator
Working Temperature	-20°C to +65°C (-4°F to 149°F)
Working Humidity	10% to 90% (Non Condensing)
Dimensions	115×44×22mm (4.53×1.73×0.87inch)
Tampering Alarm	Support
Water-proof	IP65
Installing Method	Wall mounting with screws. The Gang Box is not supported.