

# GS-P857-F28

## 5MP UHD IR Dome IP Camera



Image Sensor	1/2.8" Sony CMOS
Effective Pixels	5 megapixels
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual

BLC/HLC	Support
DNR	2D/3D DNR
Other	AGC,Motion Detection,Privacy Mask,Flip ,OSD overlay
Video Standard	H.264/H.265
Video Resolution	Main Stream: 25fps@5MP(2592x1944)/4MP(2592x1520)/3MP, 30fps@1080P/720P Sub stream: 25fps@D1/VGA/360P/CIF, etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
Built-in Mic	Optional
OSD Overlay	Title and Time overlay
IR Led	18 pcs IR Led
IR Distance	30M
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.

P2P	Yes
Web	IE , Firefox (32bit esr), etc.
Media	CMS, Android, IOS
On-VIF	17.06 compatible
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC $\pm$ 10%
Power Consumption	< 8 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH