

Key Features
Support POE Power manage
Support Cloud Upgrade & Cloud Storage
Support H.265+
Support up to 12MP IPC
Support smart detection & smart playback
Support Event stream
Support Corridor

Model
Chipset
Video & Audio Input
IP Video Input
Two Way Talk
Video & Audio Output
HDMI
VGA
Audio Output
Recording
Compression
Resolution
Bit Rate
Playback & Backup
Playback Resolution
Decoding Capability
Synchronous Playback
Playback Mode
Backup Mode
Advanced Features
Smart Detection
Smart Playback
Cloud Storage
Cloud Upgrade
Network
incoming Bandwidth
outgoing Bandwidth
Ethernet
Network Function
Smart Phone
Hard Disk
SATA
Capacity

External Interface
POE Interface
POE power
USB Interface
Alarm In
Alarm Out
General
Power Supply
Power Consumption
Working Environment
Dimension (W×D×H)
Weight



NVR401-4P4-NB
Nova98631
4ch
1ch, RCA
1ch, resolution:4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720 /60Hz
1ch, resolution:1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz
1ch, RCA
H.265+/H.265/H.264+/H.264
8MP/5MP/4MP/3MP/1080P/720P/D1/CIF /QCIF
64Kbps~10Mbps
8MP/5MP/4MP/3MP/1080P/720P/D1/CIF /QCIF
1CH 8Mp@30fps 2CH 6Mp@30fps 2CH 5Mp@30fps 3CH 4Mp@30fps 6CH 1080P@30fps
4ch
Smart Playback/Normal/Time Division/ Label/ Event/ Log playback
USB Device/Network
Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection, Human Detection,Vehicle Detection,SMD,PP
Face detection/Line Crossing/Are Intrusion/Motion Detection/Human Detection/Vehicle Detection
Support
Support
40Mbps
80Mbps
1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface
HTTPs, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF
IOS(iPhone, iPad), Android(Phone, Pad)
1 SATA interface
Up to 14TB capacity for each HDD

4 independent 10 /100 Mbps PoE Ethernet interfaces
45W (Each PoE port is max 30W)
Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0
NA
NA
DC48V 1.36A
≤10W(without HDD and POE)
-10°C~+55°C / 10%~90%RH
250x230x45mm
≤1.6Kg