



Model
Chipset
Video & Audio Input
IP Video Input
Audio input
Video & Audio Output
HDMI
VGA
Audio Output
Recording
Compression
Resolution
Playback & Backup
Playback Resolution
Decoding Capability
Synchronous Playback
Playback Mode
Backup Mode
Advanced Features
Smart Detection by Camera
Smart Playback
Cloud Storage
Cloud Upgrade
Network
Incoming Bandwidth
Outgoing Bandwidth
Ethernet
Network Function
Smart Phone
Hard Disk
SATA
Capacity
External Interface
USB Interface
eSata
RS 485
Alarm In
Alarm Out
General
Power Supply

Power Consumption
Working Environment
Dimension (W×D×H)
Weight

NVR604-32-NB
NT98336-E
32ch
1-ch, RCA
HDMI 1 : 4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz
HDMI 2 : 1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz
1920×1080/60Hz,1280×1024/60Hz, 1280×720/60Hz
2-ch, RCA
H.265+/H.265/H.264+/H.264
12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF /QCIF
12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF /QCIF
2ch@12M 20fps
4ch@8M 30fps
6ch@5M 30fps
8ch@4M 30fps
16ch@1080P 30fps
16ch
Smart Playback/Normal/Time Division/ Label/ Event/ Picture Playback
USB Device/Network/eSATA
Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection, SMD,PP
Face detection/Line Crossing/Are Intrusion/Motion Detection/Human Detection/Vehicle Detection
Support
Support
320Mbps
256Mbps
2 x RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
HTTPs, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF
IOS(iPhone, iPad), Android(Phone, Pad)
8 SATA interface
Up to 18TB capacity for each HDD
Front panel: 2 × USB 2.0
Rear panel: 2 × USB 3.0
1 x eSATA
2
16-ch
4-ch
AC 100~240V

≤20W(without HDD)
-10°C~+55°C / 10%~90%RH
440×452×90mm
7.9kg